




RTA - 600



Vridi ac-1000




Tecno - BF630e



Biolitenet



ACTA tek 31



ACTA tek



ZK Soft F-8



Walkie - Talkie System



POS Equipment



POS Roll



Wristband Label



Wristband Label




Baby Leg Barcode Tag



Metal Detector



Metal Detector



Arch Way Metal Detector



Detacher, Hard & Soft Tag

Blank Proximity ID CARD




Fire Alarm Accessories



Fire Alarm Control Panel, Zeta



Zebra, 105SL



Zebra, S4M



Zebra, S600



Zebra, TLP 2488



Barcode Label



Barcode Ribbon



Barcode Scanner & Portable Data Collector


Barcode System's Solution



Library Security System



Deactivation Pad



EAS Gate (Anti Shop Lifting)



VTKC-EAS



Library Security Tag



Hard Tag & Soft Tag

Contorl Unit, Paradox, Canada.

Fire & Burglar Alarm Security System



ID Card Printing Solution



ID Card



ID Card Printer




Hidden Camera



DVR CARD CP-9808A-L



Standalone DVR



Radio Link System

Place of Origin: Florida United States
wireless ap/cpe, outdoor 802.11a/n 300mw,
100mbps+ of real tcp/ip throughput over outdoor
multi-km links. wireless ap/cpe, outdoor 802.11
a/n 300mw, 100mbps+ of real tcp/ip throughput
over tcp/ip throughput over outdoor multi-km
links processor specs: atheros soc, mips 24 kc, 400mhz
memory information: 32mb sdram, 8mb flash



EAS Gate (Anti Shop Lifting)

Frequency 8.2MHz, Dimension 1550mm*420mm*60mm
Temperature rang 0°C~45°C, Material Aluminum Alloy
Modulation Frequency 150,160,170,180

Library Security System

Material : Good quality crystal plate, Width: 400mm
Height : 1,500mm, Thickness : 25mm
Standard frequency : 50Hz, Detection magnetic stripe : 6cm
Maximum detection Range : 90cm, Standard detection Range : 75cm
Work frequency : 2KHz, Detection height : 1,700mm



Instant Power Supply (IPS)


Capacity : 400VA, Watt : 320W, Input Voltage : 140V-280V
Input Frequency : 50Hz, Output Voltage : 230AC/50Hz Over
Load : 340W, Battery : 01 Pc Rangs power Battery 12V Battery
(RPV-100), Transfer Time : 10ms Back up Time : 2hrs, Battery
Charging Time : 10 hrs, LCD Display : Yes

Advanced Software For Office, Industry & Departmental Store

- ◆ Customized Attendance & Leave Management with payroll / Salary Software.
- ◆ Customized Inventory Management.
- ◆ Customized Fixed Asset Tracking Software.
- ◆ Customized Barcode Generating Software.




Camera Avetech KPC-133, Taiwan
1/3" Color sensor with SONY effio DSP
Number of Pixels-512
Resolution-520 TV lines
Effective Range-15 meter
Lens-3.6mm



Camera Avetech-Taiwan
1/3" color sensor with SONY effio DSP
Number of pixel: 771 (H) x 492 (V) <NTSC>
753 (H) x 582 (V) <PAL>
Effective Range-15 meter, Resolution : 600TVL
Lens- f3.8-19.55 vari-focal lens



Camera Avetech KPC-138-9, Taiwan
1/3" HR color CCD image sensor
Number of Pixels: 768(H) x 494(V) <NTSC> / 753(H) x 582(V)
Resolution: 420 TVL
Effective Range : Over 30 Meters
Lens: 3.6mm / F2.0 Lens Angle: 92.6°



IR/Night vision Camera, China
1/3" HR color CCD image
Number of Pixels-771
Resolution- 520 TV line
Effective Range-15 meter
Lens-3.6mm



Camera YHDO 555LT
1/3" COLOR SONY
Number of Pixels- PAL: 512(H)x582(V)
NTSC:512(H)x492(V), Resolution- 450TV Line
Effective Range-25 meter
Lens-16mm,6mm/8mm/12mm(Optional)





PTZ Camera, Taiwan
Pan, tilt, and zoom cameras
They can pan (move left and right), tilt (move up and down)
rotate 360 degrees and view an object
A camera's motion is remotely controlled with a keyboard



Camera Avetech AVN-212Z, Taiwan
1/3" Color CCD Network Camera (with H.264, ONVIF)
Hybrid digital / analog video output. ONVIF standard
supported to simplify system integration. It is friendly to use
by wizard with browser Motion detection



Camera Avetech APM-J011, Taiwan
Two-way audio, Remote Pan/Tilt rotate, Indoor 10 LED
IR distance 10-15M. Motion detection, email alert, FTP upload
iphone, 3G phone, Smartphone supported Multi-language
Firefox, Safari, Google browser Color Box: 210*125*195mm



IP Base HTA-830

Dual function for Access Control and Basic Time & Attendance.
Standalone network operation, expandable to 255 sets. Memory
capacity 4,096 cardholders 2,048 events. Swipe card, pin code or
card + pin code access mode (Door IN) slave reader or exit button.
(Door OUT) Duress card duress code, secret duress alarm Anti pass
back for RAC-900. 90% memory full warning RTC (Real Time
Clock) ensures accurate time regardless power outages.



Pegasus 6750, Taiwan


Access Valid access granted in less than 10-15cm Mounting
Surface mount On-line RS-232C, RS-422 or RS-485 wiegand
output Transmission rate 300-19,200 bps, N,8,1 (default 4,800 bps)
Power source 12V DC Operating technologies Fully completed Access
control & Time attendance functions




Pegasus T-7, Taiwan
Smart TCP/IP based access reader, slim and sleek
size for narrow door frames. Power over Ethernet
(PoE) and direct look relay Multi color LED
multi-tone buzzer for indication up to 40,000
users, 50,000 logs switchable wit



Zk Software X-638, China
User capacity: 2200
ID Card storage: 10000
Transaction storage : 50000
Verification mode: fingerprint, password, ID Card.
Resing current: 350mA, working current:400mA



IP Base Zk-103
Reader module: ID Card Reader Module (125KHZ)
Paradox SP-5500, Canada
10-Zone Hardwired LED Keypad Module (Horizontal) Supports
Stay/D Mode, 10-zone LED display Separate Arm, Sleep, Stay
and Off LEDs per partition Patented Key Light display (button
lights up to indicate an open zone) 1 keypad zone input
Independently set chime zones 7 one-touch action buttons
3 keypad-activated panic alarms Adjustable backlight, Connects to
4-wire communication bus Compatible



Paradox SP-5500



PANASONIC PABX SYSTEM
KX-TDE 200 - PANASONIC PABX SYSTEM, Malaysia
PA / Sound System, Toa-Japan

The KX-TDE 200 offer new, standard-equipped IP functions that boost efficiency and lower
For companies planning to a full-IP system, Panasonic IP-PBX system offer a scalable
easy to use platform that adapts to a wide range of business field for feature expansion
so they allow IP systems to be integrated with conventional telecom system such as ISDN and analogue lines
Depending on the office environment it may be difficult to switch an existing traditional telecom line to a full
IP system all at once due to time and cost restrictions The KX-TDE 100/200 response flexibly to needs



RAC-900



IP Base RAC-960

